

107.1 - Primary Gas Mixtures

These SRMs are for calibrating equipment and apparatus used to measure various components of gas mixtures and atmospheric pollutants. The typical gas mixture is supplied in a DOT 3AL specification aluminum (6061 alloy) cylinder with a nominal pressure exceeding 12.4 mPa that provides the user with approximately 0.73m³ of usable mixture. Due to increasing customer demand, these primary gas mixtures are in short supply and may not be readily available for sale. In such cases, a NIST traceable reference gas described below may be substituted.

A NIST Traceable Reference Material (NTRM) is a reference material produced by a commercial supplier with a well-defined traceability to NIST. This traceability is established via criteria and protocols defined by NIST that are tailored to meet the needs of the metrological community to be served. The NTRM concept was established to allow NIST to respond to the increasing needs for high quality reference materials by leveraging its relatively fixed human and financial resources with secondary reference material producers. Reference material producers adhering to NIST defined protocol requirements are allowed to use the NTRM trademark to identify their product.

The gas NTRM program was established in 1992 in partnership with the U.S. EPA and specialty gas companies as a means for providing end-users with the wide variety of certified gas standards needed to implement the Emissions Trading provision of the 1990 Clean Air Act. Gas NTRMs are produced and distributed by specialty gas companies with NIST oversight of the production and maintenance, and direct involvement in the analysis. NTRMs can be developed for any pollutant, concentration, and balance gas combination for which a NIST primary standard or SRM exists. The gas standards prepared according to this program are related, within known limits of uncertainty, to specific gaseous primary standards maintained by NIST.

Technical Contact: franklin.guenther@nist.gov.

PLEASE NOTE: The tables are presented to facilitate comparisons among a family of materials to help customers select the best SRM for their needs. For specific values and uncertainties, the certificate is the only official source.

SRM	Description	Unit of Issue	Certified Component	Nominal Amount-of-substance fraction
1658a	Methane in Air (Nominal 1 $\mu\text{mol/mol}$)	cylinder	1 $\mu\text{mol/mol}$	CH ₄
1659a	Methane in Air (Nominal 10 $\mu\text{mol/mol}$)	cylinder	CH ₄	10 $\mu\text{mol/mol}$
1660a	Methane and Propane in Air (Nominal: Methane 4 $\mu\text{mol/mol}$; Propane 1 $\mu\text{mol/mol}$)	cylinder	CH ₄ : C ₃ H ₈	4:1 $\mu\text{mol/mol}$
1661a'	Sulfur Dioxide in Nitrogen (Nominal 500 $\mu\text{mol/mol}$)	cylinder	SO ₂	500 $\mu\text{mol/mol}$
1662a'	Sulfur Dioxide in Nitrogen (Nominal 1000 $\mu\text{mol/mol}$)	cylinder	SO ₂	1000 $\mu\text{mol/mol}$
1663a'	Sulfur Dioxide in Nitrogen (Nominal 1500 $\mu\text{mol/mol}$)	cylinder	SO ₂	1500 $\mu\text{mol/mol}$
1664a'	Sulfur Dioxide in Nitrogen (Nominal 2500 $\mu\text{mol/mol}$)	cylinder	SO ₂	2500 $\mu\text{mol/mol}$
1665b	Propane in Air (Nominal 3 $\mu\text{mol/mol}$)	cylinder	C ₃ H ₈	3 $\mu\text{mol/mol}$
1666b	Propane in Air (Nominal 10 $\mu\text{mol/mol}$)	cylinder	C ₃ H ₈	10 $\mu\text{mol/mol}$
1667b	Propane in Air (Nominal 50 $\mu\text{mol/mol}$)	cylinder	C ₃ H ₈	50 $\mu\text{mol/mol}$
1668b'	Propane in Air (Nominal 100 $\mu\text{mol/mol}$)	cylinder	C ₃ H ₈	100 $\mu\text{mol/mol}$
1669b	Propane in Air (Nominal 500 $\mu\text{mol/mol}$)	cylinder	C ₃ H ₈	500 $\mu\text{mol/mol}$
1674b'	Carbon Dioxide in Nitrogen (Nominal 7 % mol/mol)	cylinder	CO ₂	7 % mol/mol
1676	Carbon Dioxide in Air (Nominal 365 $\mu\text{mol/mol}$)	cylinder	CO ₂	365 $\mu\text{mol/mol}$
1677c'	Carbon Monoxide in Nitrogen (Nominal 10 $\mu\text{mol/mol}$)	cylinder	CO	10 $\mu\text{mol/mol}$
1678c'	Carbon Monoxide in Nitrogen (Nominal 50 $\mu\text{mol/mol}$)	cylinder	CO	50 $\mu\text{mol/mol}$
1679c'	Carbon Monoxide in Nitrogen (Nominal 100 $\mu\text{mol/mol}$)	cylinder	CO	100 $\mu\text{mol/mol}$
1680b'	Carbon Monoxide in Nitrogen (Nominal 500 $\mu\text{mol/mol}$)	cylinder	CO	500 $\mu\text{mol/mol}$
1681b'	Carbon Monoxide in Nitrogen (Nominal 1000 $\mu\text{mol/mol}$)	cylinder	CO	1000 $\mu\text{mol/mol}$
1683b'	Nitric Oxide in Nitrogen (Nominal 50 $\mu\text{mol/mol}$)	cylinder	NO	50 $\mu\text{mol/mol}$
SRM>	Description	Unit of Issue	Certified Component	Nominal Amount-of-substance fraction
1684b'	Nitric Oxide in Nitrogen (Nominal 100 $\mu\text{mol/mol}$)	cylinder	NO	100 $\mu\text{mol/mol}$

107.1 - Primary Gas Mixtures

These SRMs are for calibrating equipment and apparatus used to measure various components of gas mixtures and atmospheric pollutants. The typical gas mixture is supplied in a DOT 3AL specification aluminum (6061 alloy) cylinder with a nominal pressure exceeding 12.4 mPa that provides the user with approximately 0.73m3 of usable mixture. Due to increasing customer demand, these primary gas mixtures are in short supply and may not be readily available for sale. In such cases, a NIST traceable reference gas described below may be substituted.

A NIST Traceable Reference Material (NTRM) is a reference material produced by a commercial supplier with a well-defined traceability to NIST. This traceability is established via criteria and protocols defined by NIST that are tailored to meet the needs of the metrological community to be served. The NTRM concept was established to allow NIST to respond to the increasing needs for high quality reference materials by leveraging its relatively fixed human and financial resources with secondary reference material producers. Reference material producers adhering to NIST defined protocol requirements are allowed to use the NTRM trademark to identify their product.

The gas NTRM program was established in 1992 in partnership with the U.S. EPA and specialty gas companies as a means for providing end-users with the wide variety of certified gas standards needed to implement the Emissions Trading provision of the 1990 Clean Air Act. Gas NTRMs are produced and distributed by specialty gas companies with NIST oversight of the production and maintenance, and direct involvement in the analysis. NTRMs can be developed for any pollutant, concentration, and balance gas combination for which a NIST primary standard or SRM exists. The gas standards prepared according to this program are related, within known limits of uncertainty, to specific gaseous primary standards maintained by NIST.

Technical Contact: franklin.guenther@nist.gov

PLEASE NOTE: The tables are presented to facilitate comparisons among a family of materials to help customers select the best SRM for their needs. For specific values and uncertainties, the certificate is the only official source.



107.1 - Primary Gas Mixtures

These SRMs are for calibrating equipment and apparatus used to measure various components of gas mixtures and atmospheric pollutants. The typical gas mixture is supplied in a DOT 3AL specification aluminum (6061 alloy) cylinder with a nominal pressure exceeding 12.4 mPa that provides the user with approximately 0.73m³ of usable mixture. Due to increasing customer demand, these primary gas mixtures are in short supply and may not be readily available for sale. In such cases, a NIST traceable reference gas described below may be substituted.

A NIST Traceable Reference Material (NTRM) is a reference material produced by a commercial supplier with a well-defined traceability to NIST. This traceability is established via criteria and protocols defined by NIST that are tailored to meet the needs of the metrological community to be served. The NTRM concept was established to allow NIST to respond to the increasing needs for high quality reference materials by leveraging its relatively fixed human and financial resources with secondary reference material producers. Reference material producers adhering to NIST defined protocol requirements are allowed to use the NTRM trademark to identify their product.

The gas NTRM program was established in 1992 in partnership with the U.S. EPA and specialty gas companies as a means for providing end-users with the wide variety of certified gas standards needed to implement the Emissions Trading provision of the 1990 Clean Air Act. Gas NTRMs are produced and distributed by specialty gas companies with NIST oversight of the production and maintenance, and direct involvement in the analysis. NTRMs can be developed for any pollutant, concentration, and balance gas combination for which a NIST primary standard or SRM exists. The gas standards prepared according to this program are related, within known limits of uncertainty, to specific gaseous primary standards maintained by NIST.

Technical Contact: franklin.guenther@nist.gov.

PLEASE NOTE: The tables are presented to facilitate comparisons among a family of materials to help customers select the best SRM for their needs. For specific values and uncertainties, the certificate is the only official source.

1685b [*]	Nitric Oxide in Nitrogen (Nominal 250 µmol/mol)	cylinder	NO	250 µmol/mol
1686b [*]	Nitric Oxide in Nitrogen (Nominal 500 µmol/mol)	cylinder	NO	500 µmol/mol
1687b [*]	Nitric Oxide in Nitrogen (Nominal 1000 µmol/mol)	cylinder	NO	1000 µmol/mol
1693a [*]	Sulfur in Nitrogen (Nominal 50 µmol/mol)	cylinder	SO ₂	50 µmol/mol
1694a [*]	Sulfur Dioxide in Nitrogen (Nominal 100 µmol/mol)	cylinder	SO ₂	100 µmol/mol
1696a [*]	Sulfur Dioxide in Nitrogen (Nominal 3500 µmol/mol)	cylinder	SO ₂	3500 µmol/mol
1800b	Eighteen Non-Methane Hydrocarbon Compounds in Nitrogen (Nominal 5 nmol/mol)	6 L Water Volume Cyl	(Eighteen components in small cylinder)	5 nmol/mol
1804c	Toxic Volatile Organic Compounds in Nitrogen (Nominal 5.0 nmol/mol)	cylinder	(Thirty components)	5 nmol/mol
2612a	Carbon Monoxide in Air (Nominal 10 µmol/mol)	cylinder	CO	10 µmol/mol
2613a	Carbon Monoxide in Air (Nominal 20 µmol/mol)	cylinder	CO	20 µmol/mol
2614a	Carbon Monoxide in Air (Nominal 42 µmol/mol)	cylinder	CO	42 µmol/mol
2617	Carbon Dioxide in Nitrogen (Nominal 500 µmol/mol)	cylinder	CO ₂	500 µmol/mol
2619a	Carbon Dioxide in Nitrogen (Nominal 0.5 % mol/mol)	cylinder	CO ₂	0.5 % mol/mol
2620a	Carbon Dioxide in Nitrogen (Nominal 1.0 % mol/mol)	cylinder	CO ₂	1.0 % mol/mol
2621a	Carbon Dioxide in Nitrogen (Nominal 1.5 % mol/mol)	cylinder	CO ₂	1.5 % mol/mol
2622a	Carbon Dioxide in Nitrogen (Nominal 2.0 % mol/mol)	cylinder	CO ₂	2.0 % mol/mol
2623a	Carbon Dioxide in Nitrogen (Nominal 2.5 % mol/mol)	cylinder	CO ₂	2.5 % mol/mol
2624a	Carbon Dioxide in Nitrogen (Nominal 3.0 % mol/mol)	cylinder	CO ₂	3.0 % mol/mol
2625a [*]	Carbon Dioxide in Nitrogen (Nominal 3.5 % mol/mol)	cylinder	CO ₂	3.5 % mol/mol

SRM>	Description	Unit of Issue	Certified Component	Nominal Amount-of-substance fraction
2627a	Nitric Oxide in Nitrogen (Nominal 5 µmol/mol)	cylinder	NO	5 µmol/mol
2628a	Nitric Oxide in Nitrogen (Nominal 10 µmol/mol)	cylinder	NO	10 µmol/mol
2629a [*]	Nitric Oxide in Nitrogen (Nominal 20 µmol/mol)	each	NO	20 µmol/mol
2630 [*]	Nitric Oxide in Nitrogen (Nominal 1500 µmol/mol)	each	NO	1500 µmol/mol

107.1 - Primary Gas Mixtures

These SRMs are for calibrating equipment and apparatus used to measure various components of gas mixtures and atmospheric pollutants. The typical gas mixture is supplied in a DOT 3AL specification aluminum (6061 alloy) cylinder with a nominal pressure exceeding 12.4 mPa that provides the user with approximately 0.73m3 of usable mixture. Due to increasing customer demand, these primary gas mixtures are in short supply and may not be readily available for sale. In such cases, a NIST traceable reference gas described below may be substituted.

A NIST Traceable Reference Material (NTRM) is a reference material produced by a commercial supplier with a well-defined traceability to NIST. This traceability is established via criteria and protocols defined by NIST that are tailored to meet the needs of the metrological community to be served. The NTRM concept was established to allow NIST to respond to the increasing needs for high quality reference materials by leveraging its relatively fixed human and financial resources with secondary reference material producers. Reference material producers adhering to NIST defined protocol requirements are allowed to use the NTRM trademark to identify their product.

The gas NTRM program was established in 1992 in partnership with the U.S. EPA and specialty gas companies as a means for providing end-users with the wide variety of certified gas standards needed to implement the Emissions Trading provision of the 1990 Clean Air Act. Gas NTRMs are produced and distributed by specialty gas companies with NIST oversight of the production and maintenance, and direct involvement in the analysis. NTRMs can be developed for any pollutant, concentration, and balance gas combination for which a NIST primary standard or SRM exists. The gas standards prepared according to this program are related, within known limits of uncertainty, to specific gaseous primary standards maintained by NIST.

Technical Contact: franklin.guenther@nist.gov

PLEASE NOTE: The tables are presented to facilitate comparisons among a family of materials to help customers select the best SRM for their needs. For specific values and uncertainties, the certificate is the only official source.



107.1 - Primary Gas Mixtures

These SRMs are for calibrating equipment and apparatus used to measure various components of gas mixtures and atmospheric pollutants. The typical gas mixture is supplied in a DOT 3AL specification aluminum (6061 alloy) cylinder with a nominal pressure exceeding 12.4 mPa that provides the user with approximately 0.73m³ of usable mixture. Due to increasing customer demand, these primary gas mixtures are in short supply and may not be readily available for sale. In such cases, a NIST traceable reference gas described below may be substituted.

A NIST Traceable Reference Material (NTRM) is a reference material produced by a commercial supplier with a well-defined traceability to NIST. This traceability is established via criteria and protocols defined by NIST that are tailored to meet the needs of the metrological community to be served. The NTRM concept was established to allow NIST to respond to the increasing needs for high quality reference materials by leveraging its relatively fixed human and financial resources with secondary reference material producers. Reference material producers adhering to NIST defined protocol requirements are allowed to use the NTRM trademark to identify their product.

The gas NTRM program was established in 1992 in partnership with the U.S. EPA and specialty gas companies as a means for providing end-users with the wide variety of certified gas standards needed to implement the Emissions Trading provision of the 1990 Clean Air Act. Gas NTRMs are produced and distributed by specialty gas companies with NIST oversight of the production and maintenance, and direct involvement in the analysis. NTRMs can be developed for any pollutant, concentration, and balance gas combination for which a NIST primary standard or SRM exists. The gas standards prepared according to this program are related, within known limits of uncertainty, to specific gaseous primary standards maintained by NIST.

Technical Contact: franklin.guenther@nist.gov

PLEASE NOTE: The tables are presented to facilitate comparisons among a family of materials to help customers select the best SRM for their needs. For specific values and uncertainties, the certificate is the only official source.

2631a*	Nitric Oxide in Nitrogen (Nominal 3000 µmol/mol)	cylinder	NO	3000 µmol/mol
2635a*	Carbon Monoxide in Nitrogen (Nominal 25 µmol/mol)	cylinder	CO	
2636a*	Carbon Monoxide in Nitrogen (Nominal 250 µmol/mol)	cylinder	CO	250 µmol/mol
2637a*	Carbon Monoxide in Nitrogen (Nominal 2500 µmol/mol)	cylinder	CO	2500 µmol/mol
2638a*	Carbon Monoxide in Nitrogen (Nominal 5000 µmol/mol)	cylinder	CO	5000 µmol/mol
2639a	Carbon Monoxide in Nitrogen (Nominal 1 % mol/mol)	cylinder	CO	1 % mol/mol
2640a	Carbon Monoxide in Nitrogen (Nominal 2 % mol/mol)	cylinder	CO	2 % mol/mol
2641a	Carbon Monoxide in Nitrogen (Nominal 4 % mol/mol)	cylinder	CO	4 % mol/mol
2642a*	Carbon Monoxide in Nitrogen (Nominal 8 % mol/mol)	cylinder	CO	8 % mol/mol
2644a	Propane in Nitrogen (Nominal 250 µmol/mol)	cylinder	C ₃ H ₈	250 µmol/mol
2646a	Propane in Nitrogen (Nominal 1000 µmol/mol)	cylinder	C ₃ H ₈	1000 µmol/mol
2647a	Propane in Nitrogen (Nominal 2500 µmol/mol)	cylinder	C ₃ H ₈	2500 µmol/mol
2657a*	Oxygen in Nitrogen (Nominal 2 % mol/mol)	cylinder	O ₂	2 % mol/mol
2658a*	Oxygen in Nitrogen (Nominal 10 % mol/mol)	cylinder	O ₂	10 % mol/mol
2659a*	Oxygen in Nitrogen (Nominal 21 % mol/mol)	cylinder	O ₂	21 % mol/mol
2660a*	Total Oxides of Nitrogen (NO _x) in Air (Nominal 100 µmol/mol)	cylinder	NO _x	100 µmol/mol

SRM>	Description	Unit of Issue	Certified Component	Nominal Amount-of-substance fraction
2730	Hydrogen Sulfide in Nitrogen (Nominal 5 µmol/mol)	cylinder	H ₂ S	5 µmol/mol
2731	Hydrogen Sulfide in Nitrogen (Nominal 20 µmol/mol)	cylinder	H ₂ S	20 µmol/mol
2735	Nitric Oxide in Nitrogen (Nominal 800 µmol/mol)	cylinder	NO	800 µmol/mol
2737	Nitric Oxide in Nitrogen (500 nmol/mol)	cylinder	NO	500 µmol/mol
2738	Nitric Oxide in Nitrogen (Nominal 1000 nmol/mol)	cylinder	NO	1000 µmol/mol
2740a	Carbon Monoxide in Nitrogen (Nominal 10 % mol/mol)	cylinder	CO	10 % mol/mol
2741a	Carbon Monoxide in Nitrogen (Nominal 13 % mol/mol)	cylinder	CO	13 % mol/mol
2745*	Carbon Dioxide in Nitrogen (Nominal 16 % mol/mol)	cylinder	CO ₂	16 % mol/mol

107.1 - Primary Gas Mixtures

These SRMs are for calibrating equipment and apparatus used to measure various components of gas mixtures and atmospheric pollutants. The typical gas mixture is supplied in a DOT 3AL specification aluminum (6061 alloy) cylinder with a nominal pressure exceeding 12.4 mPa that provides the user with approximately 0.73m3 of usable mixture. Due to increasing customer demand, these primary gas mixtures are in short supply and may not be readily available for sale. In such cases, a NIST traceable reference gas described below may be substituted.

A NIST Traceable Reference Material (NTRM) is a reference material produced by a commercial supplier with a well-defined traceability to NIST. This traceability is established via criteria and protocols defined by NIST that are tailored to meet the needs of the metrological community to be served. The NTRM concept was established to allow NIST to respond to the increasing needs for high quality reference materials by leveraging its relatively fixed human and financial resources with secondary reference material producers. Reference material producers adhering to NIST defined protocol requirements are allowed to use the NTRM trademark to identify their product.

The gas NTRM program was established in 1992 in partnership with the U.S. EPA and specialty gas companies as a means for providing end-users with the wide variety of certified gas standards needed to implement the Emissions Trading provision of the 1990 Clean Air Act. Gas NTRMs are produced and distributed by specialty gas companies with NIST oversight of the production and maintenance, and direct involvement in the analysis. NTRMs can be developed for any pollutant, concentration, and balance gas combination for which a NIST primary standard or SRM exists. The gas standards prepared according to this program are related, within known limits of uncertainty, to specific gaseous primary standards maintained by NIST.

Technical Contact: franklin.guenther@nist.gov

PLEASE NOTE: The tables are presented to facilitate comparisons among a family of materials to help customers select the best SRM for their needs. For specific values and uncertainties, the certificate is the only official source.



107.1 - Primary Gas Mixtures

These SRMs are for calibrating equipment and apparatus used to measure various components of gas mixtures and atmospheric pollutants. The typical gas mixture is supplied in a DOT 3AL specification aluminum (6061 alloy) cylinder with a nominal pressure exceeding 12.4 mPa that provides the user with approximately 0.73m3 of usable mixture. Due to increasing customer demand, these primary gas mixtures are in short supply and may not be readily available for sale. In such cases, a NIST traceable reference gas described below may be substituted.

A NIST Traceable Reference Material (NTRM) is a reference material produced by a commercial supplier with a well-defined traceability to NIST. This traceability is established via criteria and protocols defined by NIST that are tailored to meet the needs of the metrological community to be served. The NTRM concept was established to allow NIST to respond to the increasing needs for high quality reference materials by leveraging its relatively fixed human and financial resources with secondary reference material producers. Reference material producers adhering to NIST defined protocol requirements are allowed to use the NTRM trademark to identify their product.

The gas NTRM program was established in 1992 in partnership with the U.S. EPA and specialty gas companies as a means for providing end-users with the wide variety of certified gas standards needed to implement the Emissions Trading provision of the 1990 Clean Air Act. Gas NTRMs are produced and distributed by specialty gas companies with NIST oversight of the production and maintenance, and direct involvement in the analysis. NTRMs can be developed for any pollutant, concentration, and balance gas combination for which a NIST primary standard or SRM exists. The gas standards prepared according to this program are related, within known limits of uncertainty, to specific gaseous primary standards maintained by NIST.

Technical Contact: franklin.guenther@nist.gov

PLEASE NOTE: The tables are presented to facilitate comparisons among a family of materials to help customers select the best SRM for their needs. For specific values and uncertainties, the certificate is the only official source.

2750	Methane in Air (Nominal 50 μmol/mol)	cylinder	CH4	50 μmol/mol
2751	Methane in Air (Nominal 100 μmol/mol)	cylinder	CH4	100 μmol/mol
2764	Propane in Air (Nominal 0.25 μmol/mol)	cylinder	C3H8	0.25 μmol/mol
2765	Propane in Air (Nominal 100 nmol/mol)	cylinder	C3H8	100 nmol/mol

* Those SRMs that are marked "*" are available as [NTRMs](#) from commercial suppliers.

107.1 - Primary Gas Mixtures

These SRMs are for calibrating equipment and apparatus used to measure various components of gas mixtures and atmospheric pollutants. The typical gas mixture is supplied in a DOT 3AL specification aluminum (6061 alloy) cylinder with a nominal pressure exceeding 12.4 mPa that provides the user with approximately 0.73m3 of usable mixture. Due to increasing customer demand, these primary gas mixtures are in short supply and may not be readily available for sale. In such cases, a NIST traceable reference gas described below may be substituted.

A NIST Traceable Reference Material (NTRM) is a reference material produced by a commercial supplier with a well-defined traceability to NIST. This traceability is established via criteria and protocols defined by NIST that are tailored to meet the needs of the metrological community to be served. The NTRM concept was established to allow NIST to respond to the increasing needs for high quality reference materials by leveraging its relatively fixed human and financial resources with secondary reference material producers. Reference material producers adhering to NIST defined protocol requirements are allowed to use the NTRM trademark to identify their product.

The gas NTRM program was established in 1992 in partnership with the U.S. EPA and specialty gas companies as a means for providing end-users with the wide variety of certified gas standards needed to implement the Emissions Trading provision of the 1990 Clean Air Act. Gas NTRMs are produced and distributed by specialty gas companies with NIST oversight of the production and maintenance, and direct involvement in the analysis. NTRMs can be developed for any pollutant, concentration, and balance gas combination for which a NIST primary standard or SRM exists. The gas standards prepared according to this program are related, within known limits of uncertainty, to specific gaseous primary standards maintained by NIST.

Technical Contact: franklin.guenther@nist.gov

PLEASE NOTE: The tables are presented to facilitate comparisons among a family of materials to help customers select the best SRM for their needs. For specific values and uncertainties, the certificate is the only official source.

